

HiView 2MP ColorVu FIXED Bullet Camera

TH-B127-P



2MP / 1080P

2,8mm / 3,6mm Fix Focal Lens

Day / Night Auto Switch

White Light Distance 20M

**4 in 1 Video Output OSD Button
(TVI/AHD/CVI/CVBS)**

Auto WDR

IP66 Waterproof

0,01 Lux

24 Hours Colour

• Specification

Camera	
Image Sensor	2 MP CMOS
Signal System	PAL/NTSC
Resolution	1920 (H) × 1080 (V)
Frame Rate	TVI: 1080p@25fps/30fps CVI: 1080p@25fps/30fps AHD: 1080p@25fps/30fps CVBS: PAL/NTSC
Min. Illumination	0.01 Lux @ (F1.6, AGC ON), 0 Lux with white light
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Lens	2.8 mm/3.6 mm fixed lens
Field of View	2.8 mm, horizontal FOV: 109°, vertical FOV: 57°, diagonal FOV: 129° 3.6 mm, horizontal FOV: 87°, vertical FOV: 44°, diagonal FOV: 105°
Lens Mount	M12
Day & Night	24/7 Color Imaging
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360°
Image	
White Light	Auto/Off
Image Mode	STD/HIGH-SAT
AGC	Yes
Day/Night Mode	Color
White Balance	Auto/Manual
AE (Auto Exposure) Mode	DWDR,BLC,HLC,Global
Noise Reduction	2D DNR
Language	English
Function	Brightness, Contrast, Mirror, Sharpness, Smart Light, Saturation
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
Power Output	12 VDC
General	
Operating Conditions	-40°C to 45°C (-40°F to 113°F), Humidity: 90% or less (non-condensing)
Power Supply	12 VDC±25% <i>*You are recommended to use one power adapter to supply the power for one camera.</i>
Consumption	Max. 2.3 W
Material	Plastic
White Light Range	Up to 20 m
Dimension	162.7 mm × 70 mm × 70 mm (6.41" × 2.75" × 2.75")
Weight	Approx. 152.5 g (0.34 lb.)
Approval	
Protection	IP66